

AD-A165 219 STOCHASTIC ESTIMATION IN COMBINED ARMS LANCHESTER
MODELING OF WARFARE(U) ARMY MATERIEL SYSTEMS ANALYSIS
ACTIVITY ABERDEEN PROVING GROUND MD H E COHEN JUL 85
UNCLASSIFIED AMSAA-TR-414 F/G 15/7

STOCHASTIC ESTIMATION IN COMBINED ARMS LANCHESTER
MODELING OF WARFARE(U) ARMY MATERIEL SYSTEMS ANALYSIS
ACTIVITY ABERDEEN PROVING GROUND MD H E COHEN JUL 85
AMSAA-TR-414 F/G 15/7

1/1


UNCLASSIFIED

F/G 15/7

NL


Math Notes

1486



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A165 219



AMSAA

AD

12

TECHNICAL REPORT NO. 414

STOCHASTIC ESTIMATION IN COMBINED ARMS
LANCHESTER MODELING OF WARFARE

HERBERT E. COHEN

JULY 1985

DTIC
ELECTE
MAR 13 1986
S B D

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

U. S. ARMY MATERIEL SYSTEMS ANALYSIS ACTIVITY
ABERDEEN PROVING GROUND, MARYLAND

86 8 13 003

DTIC FILE COPY

DISPOSITION

Destroy this report when no longer needed. Do not return it to the originator.

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so specified by other official documentation.

WARNING

Information and data contained in this document are based on the input available at the time of preparation. The results may be subject to change and should not be construed as representing the DARCOM position unless so specified.

TRADE NAMES

The use of trade names in this report does not constitute an official endorsement or approval of the use of such commercial hardware or software. The report may not be cited for purposes of advertisement.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER Technical Report 414	2. GOVT ACCESSION NO. ADA 165219	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Stochastic Estimation in Combined Arms Lanchester Modeling of Warfare		5. TYPE OF REPORT & PERIOD COVERED Technical Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Herbert E. Cohen		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Director US Army Materiel Systems Analysis Activity ATTN: AMXSY-MP. Aberdeen Proving Ground, MD		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS 21005-5071 Commander US Army Materiel Command, 5001 Eisenhower Ave. Alexandria, VA 22333-0001		12. REPORT DATE
		13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution is unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Lanchester Modeling Discrete Kalman Filter Combined Arms Homogeneous Force Model Kalman - Bucy Filter Heterogeneous Force Model Kalman Filter Continuous Kalman Filter		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This present paper calls attention to the fact that stochastic estimation theory, as practiced in modern control theory, provides a method for predicting conditions on the battlefield from measurements or observations of the battle area that are themselves uncertain and where the parameters of the mathematical model are not known precisely.		

ACKNOWLEDGEMENTS

The US Army Materiel Systems Analysis Activity (AMSAA) recognizes the following individual for contributing to this report.

Peer Reviewer: Paul Kunselman

The author wishes to express his continued appreciation to the word processing group that labored over this manuscript and to John Kramar for his continued interest and encouragement in this work, to Dr. Frank Grubbs for his time in extended technical discussions on Lanchester models and to Toney Perkins on certain aspects of control as applied to land warfare models.

DTIC
ELECTE
MAR 13 1986
B

Accession For	
NTIS CBASI	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	<input type="checkbox"/>
By	
Date	
Avail	
Dist	
A-1	



The next page is blank.

CONTENTS

	PAGE
ACKNOWLEDGEMENTS	iii
REFERENCES	19
APPENDIX	21
DISTRIBUTION LIST	35

The next page is blank.

STOCHASTIC ESTIMATION IN COMBINED ARMS LANCHESTER MODELING OF WARFARE

Deterministic Lanchester models of warfare with time dependent attrition coefficients has received extensive study [1]. There does not appear to be any analytical effort to incorporate observations of the battlefield into Lanchester models. This is very surprising when one considers the vast amount of effort going on in developing techniques for observing events on the battlefield and integrating intelligence in a "fusion" center. In addition, no analytical work appears to have incorporated uncertainties in the model itself. The objective of this paper is to develop a general methodology, using stochastic estimation theory as practiced in modern control theory, for predicting conditions on the battlefield from measurements or observations of the battle area that are themselves uncertain and where the parameters of the mathematical model are not known precisely. Examples are also provided to show how the general theory can be applied to two specific problems.

Kayman: Kalman Best filters.
The fundamental Lanchester equations for homogeneous forces is given by

$$\begin{aligned}\frac{dx}{dt} &= -\alpha y \\ \frac{dy}{dt} &= -\beta x\end{aligned}\tag{1}$$

where x and y are the force strength of each side and α is the attrition of x force due to the weapon effectiveness of the y force and similarly β is the attrition coefficient of the y force due to the weapon effectiveness of the x force. Taking into consideration that the values α and β can change with time and also are not known exactly, we can incorporate the uncertainties in these parameters by adding to our model a gaussian white noise term in each equation so that equation (1) is modified as

$$\begin{aligned}\frac{dx}{dt} &= -\alpha y + w_1(t) \\ \frac{dy}{dt} &= -\beta x + w_2(t)\end{aligned}\tag{2}$$

where w_1 and w_2 are uncorrelated gaussian white noise.

Equation (2) can be written in matrix form

$$\frac{d}{dt} \begin{pmatrix} x \\ y \end{pmatrix} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix} + \begin{pmatrix} w_1(t) \\ w_2(t) \end{pmatrix}$$

or with $\underline{x} = (x, y)^T$ vector

$$\underline{A} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix} \quad \text{matrix}$$

$$\underline{w} = (w_1, w_2)^T \quad \text{vector}$$

we have

$$\frac{d\underline{x}}{dt} = \underline{A} \underline{x} + \underline{w} \quad (3)$$

where $\underline{w}(t)$ is gaussian white noise such that

$$E[\underline{w}(t)] = 0 \quad \text{for all } t$$

$$\text{cov} [\underline{w}(t), \underline{w}(\tau)] = \underline{Q} \delta(t - \tau) \quad (3a)$$

$$\text{i.e., } \underline{w} \sim N(\underline{0}, \underline{Q})$$

$$\text{with } \underline{Q} = \underline{Q}^T > 0$$

Equation (3) and (3a) represents the vector form of the homogeneous Lanchester model with "plant" noise \underline{w}

Observation over the battlefield can be similarly characterized as

$$z_1 = c_1 x + v_1$$

$$z_2 = c_2 y + v_2$$

where z_1 is the measurement of x corrupted by measurement noise v_1 , and z_2 is the measurement of y corrupted by measurement noise v_2 . If we let $\underline{z} = (z_1, z_2)^T$, $\underline{x} = (x, y)^T$ and $\underline{v} = (v_1, v_2)^T$ we have

$$\underline{z} = \underline{C} \underline{x} + \underline{v} \quad (4)$$

$$\text{with } \underline{C} = \begin{pmatrix} c_1 & 0 \\ 0 & c_2 \end{pmatrix}$$

and $\underline{v}(t) \sim N(\underline{0}, \underline{R}(t))$ gaussian white noise

such that

$$\left. \begin{aligned} E \{ \underline{v}(t) \} &= \underline{0} \quad \text{for all } t \\ \text{cov} \{ \underline{v}(t), \underline{v}(\tau) \} &= \underline{R} \delta(t - \tau) \\ \underline{R}(t) &= \underline{R}^T(t) > 0 \end{aligned} \right\} \quad (4a)$$

We also require \underline{R} to be non-singular i.e., \underline{R}^{-1} exists.

Thus the fundamental set of equations which describe the observations over the battlefield for "stochastic" homogeneous Lanchester models of warfare is given by

$$\left. \begin{aligned} \text{(System model): } \frac{d\underline{x}(t)}{dt} &= \underline{A} \underline{x}(t) + \underline{w}(t) \\ \text{(Measurement model): } \underline{z}(t) &= \underline{C} \underline{x}(t) + \underline{v}(t) \end{aligned} \right\} \quad (5)$$

where the initial state $\underline{x}(t_0)$ is modeled as a random vector since the initial conditions are not precisely known. To characterize the initial state $\underline{x}(t_0)$ we need

$$\begin{aligned} E \{ \underline{x}(t_0) \} &= \underline{\bar{x}}_0 \\ \text{cov} [\underline{x}(t_0), \underline{x}(t_0)] &= \underline{P}_0 \quad \text{initial state covariance} \\ \underline{P}_0 &= \underline{P}_0^T \succeq 0 \end{aligned} \quad (6)$$

The "plant" noise $\underline{w}(t)$ is used to model external disturbances and modeling errors in \underline{A} . Similarly, the measurement noise $\underline{v}(t)$ is used for modeling error in \underline{C} .

It is also assumed that $\underline{x}(t_0)$, $\underline{w}(t)$, and $\underline{v}(t)$ are independent for all t_0, t, τ , i.e.,

$$\left. \begin{aligned} \text{cov} [\underline{x}(t_0), \underline{w}(t)] &= \underline{0} \quad \forall t_0, t \\ \text{cov} [\underline{x}(t_0), \underline{v}(t)] &= \underline{0} \quad \forall t_0, t \\ \text{cov} [\underline{w}(t), \underline{v}(\tau)] &= \underline{0} \quad \forall t_0, \tau \end{aligned} \right\} \quad (7)$$

The flow diagram for equation (5) is shown in Figure 1.

Thus, the stochastic estimation problem is to find an estimate $\hat{\underline{x}}$ for the stochastic homogeneous Lanchester equation (5) subject to equations (3a), (4a), (6), and (7) such that, for a given set of past measurements $\underline{z}(1)$, $\underline{z}(2)$, ..., $\underline{z}(t)$, the estimate $\hat{\underline{x}}(t)$ minimizes

$$J = E \{ ||\underline{x}(t) - \hat{\underline{x}}(t)||^2 \mid \underline{z}(1), \underline{z}(2), \dots, \underline{z}(t) \} \quad (7a)$$

in the least squares sense.

It is now well known that the Kalman-Bucy filter [2, 3, 4] provides such an estimate and that $\hat{\underline{x}}$ satisfies




Figure 1.

$$\frac{d\hat{\underline{x}}}{dt} = \underline{A} \hat{\underline{x}}(t) + \underline{H} [\underline{z}(t) - \underline{C} \hat{\underline{x}}(t)] \quad (8)$$

$$\hat{\underline{x}}(t_0) = \bar{\underline{x}}_0$$

where the filter gain matrix \underline{H} is given by

$$\underline{H} = \underline{P}(t) \underline{C}^T \underline{R}^{-1}(t) \quad (9)$$

with the error covariance matrix $\underline{P}(t)$ satisfies the Riccati equation

$$\frac{d\underline{P}(t)}{dt} = \underline{A} \underline{P}(t) + \underline{P}(t) \underline{A}^T + \underline{Q} - \underline{P}(t) \underline{C}^T \underline{R}^{-1} \underline{C} \underline{P}(t) \quad (10)$$

$$\text{with } \underline{P}(t_0) = \underline{P}_0$$

The Kalman-Bucy filter can be implemented as shown in Figure 2.

The state estimate $\hat{\underline{x}}$ provides a battlefield commander with a predicted estimate of the future conditions of his force strength and that of his opponents based on available information up to the present time for a homogeneous force.

The heterogeneous or combined arms Lanchester model of warfare can be simply achieved by expanding the definition of x and y to a force structure made up of several distinct weapon systems x_i, y_j for $i = 1, 2, \dots, n, j = 1, 2, \dots, m$ such that

$$\underline{x} = (x_1, x_2, \dots, x_n, y_1, y_2, \dots, y_m)^T \quad n + m \text{ vector}$$

and

$$\underline{w} = (w_1, w_2, \dots, w_n, w_{n+1}, \dots, w_{n+m})^T \quad n + m \text{ vector}$$

$$\underline{v} = (v_1, v_2, \dots, v_n, v_{n+1}, \dots, v_{n+m})^T \quad n + m \text{ vector}$$

$$\underline{z} = (z_1, z_2, \dots, z_n, z_{n+1}, \dots, z_{n+m})^T \quad n + m \text{ vector}$$

and where the plant matrix \underline{F} takes on the form

$$\underline{F} = \begin{pmatrix} \underline{0} & \underline{A} \\ \underline{B} & \underline{0} \end{pmatrix} \quad (n + m) \times (n + m) \text{ matrix}$$

where $\underline{A}, \underline{B}$ are now matrices which represent the attrition coefficients associated with weapon y_j and x_i for $j = 1, 2, m$ and $i = 1, 2, \dots, n$.




Figure 2. KALMAN - BUCY Filter

Thus for the heterogenous case equation (5) is transformed into

$$\frac{dx}{dt} = \underline{F} \underline{x} + \underline{w} \quad (11)$$

$$\underline{z}(t) = \underline{C} \underline{x} + \underline{v}$$

Naturally, \underline{C} is similarly defined. The implementation is similar to that shown in Figure 1. All the constraints imposed on \underline{w} and \underline{v} are the same as in the homogeneous case. The optimal estimate, generated by the Kalman-Bucy filter for the heterogeneous systems, is also satisfied for equation (8) through (10). The Kalman-Bucy filter approach can also be applied to the situation in which $F(t)$ and $C(t)$ are time dependent.

Discrete System

We can transform the homogeneous system (equation (5)) to discrete time model if we use

$$\frac{dx(t)}{dt} = \lim_{\Delta t \rightarrow 0} \frac{\underline{x}(t_k) - \underline{x}(t_{k-1})}{\Delta t}$$

so that

$$\underline{x}(t_k) - \underline{x}(t_{k-1}) = \underline{A} \Delta t \underline{x}(t_{k-1}) + \Delta t \underline{w}(t_{k-1})$$

$$\underline{z}(t_k) = \underline{C} \underline{x}(t_{k-1}) + \underline{v}(t_{k-1})$$

which reduces to

$$\left. \begin{aligned} \underline{x}(t_k) &= \Phi_{k-1} \underline{x}(t_{k-1}) + \Delta t \underline{w}(t_{k-1}) \\ \underline{z}(t_k) &= \underline{C} \underline{x}(t_k) + \underline{v}(t_k) \end{aligned} \right\} \quad (12)$$

where

$$\left. \begin{aligned} \Phi_{k-1} &= \underline{I} + \underline{A} \Delta t, \\ \underline{w}_{k-1} &= \Delta t \underline{w}(t_{k-1}) \\ \underline{w}(t_k) &\sim N(\underline{0}, \underline{Q}_k) \\ \underline{Q}_k &= \underline{Q}(t)/\Delta t \\ \underline{v}(t_k) &\sim N(\underline{0}, \underline{R}_k) \\ \underline{R}_k &= \underline{R}(t)/\Delta t \end{aligned} \right\} \quad (13)$$

with initial state $\underline{x}(0)$ gaussian and $\underline{x}(0)$, $\underline{w}(t_{k-1})$, $\underline{v}(t_{k-1})$ are independent for all t, τ .

The optimal filtering problem is to determine $\underline{x}(t_{k-1})$ given a sequence of past measurements $\underline{z}(1), \underline{z}(2), \dots, \underline{z}(t_{k-1})$ where the optimal estimate is defined as the conditional mean

$$(\text{known}) \quad \hat{\underline{x}}(t_{k-1} | t_{k-1}) = E \{ \underline{x}(t_{k-1}) | \underline{z}(1), \underline{z}(2), \dots, \underline{z}(t_{k-1}) \} \quad (14)$$

where $p(\underline{x}(t_{k-1}) | \underline{z}(1), \underline{z}(2), \dots, \underline{z}(t_{k-1}))$, the conditional density function, is gaussian and known. The conditional covariance

$$(\text{known}) \quad \underline{P}(t_{k-1} | t_{k-1}) = \text{cov} [\underline{x}(t_{k-1}), \underline{x}(t_{k-1}) | \underline{z}(1), \underline{z}(2), \dots, \underline{z}(t_{k-1})] \quad (15)$$

We are interested in predicting $\underline{x}(t_k)$ given observations $\underline{z}(1), \underline{z}(2), \dots, \underline{z}(t_{k-1})$ before measurement $\underline{z}(t_k)$ is made and then to improve that estimate $\underline{x}(t_k)$ based on expanded information $\underline{z}(1), \underline{z}(2), \dots, \underline{z}(t_{k-1}), \underline{z}(t_k)$ after we have made a measurement or observation at t_k i.e., $\underline{z}(t_k)$.

The discrete Kalman filter can be summarized as follows:

State Dynamics Model:

$$\underline{x}(t_k) = \underline{\Phi}_{k-1} \underline{x}(t_{k-1}) + \underline{w}(t_{k-1})$$

$$\underline{w}(t_k) \sim N(\underline{0}, \underline{Q}_k)$$

Measurement Model

$$\underline{z}(t_k) = \underline{C} \underline{x}(t_k) + \underline{v}(t_k)$$

$$\underline{v}(t_k) \sim N(\underline{0}, \underline{R}_k)$$

Off-Line Calculations

Initialization ($t=0$):

$$\underline{P}_0 = E [(\underline{x}(0) - \hat{\underline{x}}(0)) (\underline{x}(0) - \hat{\underline{x}}(0))^T]$$

Predict Cycle:

$$\underline{P}(t_k | t_{k-1}) = \underline{\Phi}(t_{k-1}) \underline{P}(t_{k-1}) \underline{\Phi}^T(t_{k-1}) + \underline{Q}(t_{k-1})$$

Update Cycle:

$$\underline{P}(t_k | t_k) = \underline{P}(t_k | t_{k-1}) - \underline{P}(t_k | t_{k-1}) \underline{C}^T(t_k) \cdot \\ [\underline{C}(t_k) \underline{P}(t_k | t_{k-1}) \underline{C}^T(t_k) + \underline{R}(t_k)]^{-1} \underline{C}(t_k) \underline{P}(t_k | t_{k-1})$$

Filter Gain Matrix:

$$\underline{H}(t_k) = \underline{P}(t_k | t_k) \underline{C}^T(t_k) \underline{R}^{-1}(t_k)$$

On-Line Calculations:

Initialization: (t=0)

$$\hat{\underline{x}}(0|0) = E\{\underline{x}(0)\}$$

Predict Cycle:

$$\hat{\underline{x}}(t_k|t_{k-1}) = \Phi_{k-1} \hat{\underline{x}}(t_{k-1} | t_{k-1})$$

Update Cycle:

$$\hat{\underline{x}}(t_k|t_k) = \hat{\underline{x}}(t_k|t_{k-1}) + \underline{H}(t_k) \{ \underline{z}(t_k) - \underline{C}(t_k) \hat{\underline{x}}(t_k|t_{k-1}) \}$$

Innovation $\underline{r}(t_k)$

System dynamics and measurement flow diagram is given in Figure 3.

The structure of discrete time Kalman filter is shown in Figure 4.




Figure 3. Discrete System Dynamics and Measurements.




Figure 4. Discrete KALMAN-BUCY Filter.

Several examples will now be considered to demonstrate the method of computation, details of which are presented in the Appendix.

Example 1: Square law with noise in only one of the state variables.

$$\dot{x} = 0x - \alpha y$$

$$\dot{y} = \beta x + 0y + 1 w \quad (\text{noise in } y \text{ only})$$

$$z = y + v \quad (\text{observation of } y \text{ only})$$

$$\begin{pmatrix} \dot{x} \\ \dot{y} \end{pmatrix} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix} + \begin{pmatrix} 0 \\ 1 \end{pmatrix} w$$

$$z = (0 \ 1) \begin{pmatrix} x \\ y \end{pmatrix} + v$$

$$\underline{A} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix} \quad \underline{G} = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

$$\underline{H} = (0 \ 1)$$

$$E(w(t')) = 0 \quad E(v(t)) = 0$$

$$E(w(t)w(t')) = q \delta(t-t') \quad E(v(t)v(t')) = r \delta(t-t')$$

$$\underline{Q} = q \quad \underline{R} = r$$

$$E(x(0)) = 0; \quad E(y(0)) = 0$$

$$E \begin{pmatrix} x^2 & x y \\ y x & y^2 \end{pmatrix}_{t=0} = \begin{pmatrix} P_{11}(0) & P_{12}(0) \\ P_{21}(0) & P_{22}(0) \end{pmatrix} = \underline{P}(0)$$

$$\dot{\underline{P}} = \underline{A} \underline{P} + \underline{P} \underline{A}^T + \underline{G} \underline{Q} \underline{G}^T - \underline{P} \underline{H}^T \underline{R}^{-1} \underline{H} \underline{P} \quad (\text{Riccati Equation})$$

$$\underline{P} = \begin{pmatrix} P_{11} & P_{12} \\ P_{21} & P_{22} \end{pmatrix} \quad P_{21} = P_{12}$$

$$\dot{P}_{11} = -2\alpha P_{21} - \left(\frac{1}{r}\right) P_{21}^2$$

$P_{11}(0)$ given

$$\dot{P}_{12} = -\alpha P_{22} - \beta P_{11} - \left(\frac{1}{r}\right) P_{21} P_{22}$$

$P_{12}(0)$ given

$$\dot{P}_{22} = -2\beta P_{12} + q - \left(\frac{1}{r}\right) P_{22}^2$$

$P_{22}(0)$ given

Steady State:

$$\dot{P}_{11} = \dot{P}_{12} = \dot{P}_{22} = 0$$

$$\dot{P}_{11} = 0 \Rightarrow P_{21} = 0$$

$$\dot{P}_{12} = 0 \Rightarrow 0 = -\left(\alpha + \frac{1}{r} P_{21}\right) P_{22} - \beta P_{11}$$

$$\dot{P}_{22} = 0 \Rightarrow 0 = -2\beta P_{12} + q - \frac{1}{r} P_{22}^2$$

$$\text{with } P_{12} = P_{21} = 0 \Rightarrow P_{22} = (rq)^{1/2}$$

$$P_{11} = -\frac{\alpha}{\beta} P_{22} = -\left(\frac{\alpha}{\beta}\right) (rq)^{1/2}$$

$$\dot{\hat{x}} = \underline{A} \hat{x} + \underline{G} \bar{w} + \underline{P} \underline{H}^T \underline{R}^{-1} (\underline{z} - \underline{H} \hat{x}) \quad \hat{x}(0) = 0$$

or

$$\dot{\hat{x}} = (\underline{A} - \underline{K} \underline{H}) \hat{x} + \underline{K} \underline{z} \quad \underline{K} = \underline{P} \underline{H}^T \underline{R}^{-1}$$

$$\hat{x} = \begin{pmatrix} \hat{x} \\ \hat{y} \end{pmatrix}; \quad \underline{A} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix}; \quad \underline{G} = \begin{pmatrix} 0 \\ 1 \end{pmatrix} \quad \underline{H} = (0 \ 1)$$

$$\dot{\hat{x}} = -\alpha \hat{y} + \left(\frac{1}{r}\right) P_{21}(t) (z - \hat{y}) \quad \text{where } \hat{x}(0) = 0$$

$$\dot{\hat{x}} = -\alpha \hat{y} \quad \text{at steady state}$$

$$\begin{aligned} \dot{\hat{y}} &= -\beta \hat{x} + \left(\frac{1}{r} \right) P_{22}(t) (z - \hat{y}) & \hat{y}(0) &= 0 \\ &= -\beta \hat{x} + \left(\frac{q}{r} \right)^{1/2} (z - \hat{y}) & \text{at steady state} \end{aligned}$$

Summarizing the results for the case where only one state variable (y) is corrupted by noise in the systems model and measurement, the general solution satisfies the equations

$$\dot{\hat{x}} = -\alpha \hat{y} + (P_{21}(t)/r) (z - \hat{y}) \quad \hat{x}(0) = 0$$

$$\dot{\hat{y}} = -\beta \hat{x} + (P_{22}(t)/r) (z - \hat{y}) \quad \hat{y}(0) = 0$$

while the steady state equations take the form

$$\dot{\hat{x}} = -\alpha \hat{y} \quad \hat{x}(0) = 0$$

$$\dot{\hat{y}} = -\beta \hat{x} + \frac{q}{r}^{1/2} (z - \hat{y}) \quad \hat{y}(0) = 0$$

In the next example (example 2) we consider the case where the "plant" noise and measurement noise corrupts both state variables as follows.

Example 2:

$$\dot{x} = 0x - \alpha y + 1 w_1.$$

$$\dot{y} = -\beta x + 0y + 1 w_2.$$

$$z_1 = x + v_1$$

$$z_2 = y + v_2$$

$$\underline{z} = \begin{pmatrix} z_1 \\ z_2 \end{pmatrix}$$

$$\underline{x} = \begin{pmatrix} x \\ y \end{pmatrix} \quad \underline{F} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix}; \quad \underline{G} = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} = \underline{I}$$

$$\dot{\underline{x}} = \underline{A} \underline{x} + \underline{I} \underline{w}$$

$$\underline{w} = \begin{pmatrix} w_1 \\ w_2 \end{pmatrix}$$

$$\underline{z} = \underline{I} \underline{x} + \underline{v}$$

$$\underline{H} = \underline{I}; \underline{v} = \begin{pmatrix} v_1 \\ v_2 \end{pmatrix}$$

$$E(\underline{x}(0)) = \underline{0}$$

$$E(\underline{x}\underline{x}^T)_{t=0} = \underline{P}(0)$$

$$E(\underline{w}) = \underline{0}; E(\underline{w}(t) \underline{w}(t')^T) = \underline{Q}(t) \delta(t-t')$$

$$\underline{Q}(t) = \begin{pmatrix} Q_{11} & Q_{12} \\ Q_{21} & Q_{21} \end{pmatrix} \text{ assumed constant}$$

$$E(\underline{v}) = \underline{0}; E(\underline{v}(t) \underline{v}(t')^T) = \underline{R}(t) \delta(t-t'); \underline{R}(t) = \begin{pmatrix} R_{11} & R_{12} \\ R_{21} & R_{22} \end{pmatrix}$$

$$\underline{R}^{-1} = \frac{1}{|R|} \begin{pmatrix} R_{22} & -R_{12} \\ -R_{21} & R_{11} \end{pmatrix}$$

\underline{R} is assumed constant

$$|R| \neq 0$$

$$\underline{P} = \begin{pmatrix} P_{11} & P_{12} \\ P_{21} & P_{22} \end{pmatrix};$$

$$|R| = R_{11} R_{22} - R_{21} R_{12}$$

$$\underline{K} = \frac{1}{|R|} \begin{pmatrix} \xi_{11} & \xi_{12} \\ \xi_{21} & \xi_{22} \end{pmatrix} = \underline{P} \underline{H}^T \underline{R}^{-1}$$

where

$$\xi_{11} = P_{11} R_{22} - P_{12} R_{21}$$

$$\xi_{12} = P_{12} R_{11} - P_{11} R_{12}$$

$$\epsilon_{21} = P_{21} R_{22} - P_{22} R_{21}$$

$$\epsilon_{22} = P_{22} R_{11} - P_{21} R_{12}$$

$$P_{11} = \sqrt{\frac{Q_{11}}{R_{22}} |R|} \quad \text{Steady state}$$

$$P_{22} = \sqrt{\frac{Q_{22}}{R_{11}} |R|} \quad \text{Steady state}$$

$$P_{12} = P_{21} \rightarrow 0$$

The predicted state updated by measurements at an earlier time now is given by

$$\dot{\hat{\underline{x}}} = \underline{A} \hat{\underline{x}} + \underline{G} \underline{w} + \underline{P} \underline{H}^T \underline{R}^{-1} (\underline{z} - \underline{H} \hat{\underline{x}}) \quad \underline{x}(0) = 0$$

or

$$\dot{\hat{\underline{x}}} = (\underline{A} - \underline{K}) \hat{\underline{x}} + \underline{K} \underline{z}$$

$$\begin{pmatrix} \dot{\hat{x}} \\ \dot{\hat{y}} \end{pmatrix} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix} \begin{pmatrix} \hat{x} \\ y \end{pmatrix} + \frac{1}{|R|} \begin{pmatrix} \epsilon_{11} & \epsilon_{12} \\ \epsilon_{21} & \epsilon_{22} \end{pmatrix} \begin{pmatrix} z_1 - \hat{x} \\ z_2 - \hat{y} \end{pmatrix}$$

$$\dot{\hat{x}}(t) = -\alpha \hat{y}(t) + \frac{1}{|R|} \{ \epsilon_{11}(t) (z_1 - \hat{x}) + \epsilon_{12}(t) (z_2 - \hat{y}) \}$$

$$\dot{\hat{y}}(t) = -\beta \hat{x}(t) + \frac{1}{|R|} \{ \epsilon_{21}(t) (z_1 - \hat{x}) + \epsilon_{22}(t) (z_2 - \hat{y}) \}$$

where

$$\epsilon_{11}(t) = P_{11}(t) R_{22} - P_{12}(t) R_{21}$$

$$\epsilon_{12}(t) = P_{12}(t) R_{11} - P_{11}(t) R_{12}$$

$$\epsilon_{21}(t) = P_{21}(t) R_{22} - P_{22}(t) R_{21}$$

$$\epsilon_{22}(t) = P_{22}(t) R_{11} - P_{21}(t) R_{12}$$

$$\dot{\hat{x}} = \frac{-\xi_{11}(t)}{|R|} \hat{x} - \left(\alpha + \frac{\xi_{12}(t)}{|R|} \right) \hat{y} + \frac{\xi_{11}(t)}{|R|} z_1 + \frac{\xi_{12}(t)}{|R|} z_2$$

$$\dot{\hat{y}} = -\left(\beta + \frac{\xi_{21}(t)}{|R|} \right) \hat{x} - \frac{\xi_{22}(t)}{|R|} \hat{y} + \frac{\xi_{21}(t)}{|R|} z_1 + \frac{\xi_{22}(t)}{|R|} z_2$$

$$\underline{F}_2(t) = \begin{pmatrix} \frac{\xi_{11}(t)}{|R|} & -\left(\alpha + \frac{\xi_{12}(t)}{|R|} \right) \\ -\left(\beta + \frac{\xi_{21}(t)}{|R|} \right) & \frac{\xi_{22}(t)}{|R|} \end{pmatrix} = \underline{A}(t) - \underline{K}(t)$$

$$\dot{\underline{\hat{x}}} = \underline{F}_2(t) \underline{\hat{x}} + \underline{B} \underline{z}$$

$$\underline{\hat{x}} = \begin{pmatrix} \hat{x} \\ \hat{y} \end{pmatrix}; \underline{z} = \begin{pmatrix} z_1 \\ z_2 \end{pmatrix}$$

$$\underline{B} = \begin{pmatrix} \frac{\xi_{11}(t)}{|R|} & \frac{\xi_{12}(t)}{|R|} \\ \frac{\xi_{21}(t)}{|R|} & \frac{\xi_{22}(t)}{|R|} \end{pmatrix} = \underline{K}(t)$$

$$\underline{\hat{x}}(t) = \underline{\phi}(t, t_0) \underline{\hat{x}}(t_0) + \int_{t_0}^t \underline{\phi}(t, \tau) \underline{K}(\tau) \underline{z}(\tau) d\tau$$

where $\underline{\phi}(t, t_0)$ satisfies the homogeneous equation

$$\dot{\underline{\phi}}(t, t_0) = \underline{F}_2(t) \underline{\phi}(t, t_0)$$

Accordingly we have obtained either the differential equation for which the predicted estimate \hat{x} needs to satisfy or the integral solution for this estimate in terms of its transition matrix $\Phi(t, t_0)$.

In summary, there currently exists engineering techniques from the field of modern control theory that offers the commander in the field the opportunity of predicting or forecasting conditions of the force strength on the battlefield given prior information or observation on status of battle. The approach can handle any number of different weapon systems. The methodology described in this report will be applied to recently acquired data on tank duels and will be reported in a separate report.

REFERENCES

1. Taylor, J. G., Lanchester Models of Warfare, Volumes 1 and 2, OKSA, March 1983.
2. Gelb, A., Applied Optimal Estimates, MIT Press, 1974.
3. Bryson, A. E., and Ho, Y. C., Applied Optimal Control, Ginn and Company, 1969.
4. Sage, A. P., and White, C. C., Optimum Systems Control, 2nd Edition, Prentice-Hall, Inc. (1977).

APPENDIX

APPENDIX

Detailed analysis and derivations will now be presented to demonstrate the method of computation.

Example 1: Square law with noise in only one of the state variables.

$$\dot{x} = 0x - \alpha y$$

$$\dot{y} = \beta x + 0y + 1 w \quad (\text{noise in } y \text{ only})$$

$$z = y + v \quad (\text{observation of } y \text{ only})$$

$$\begin{pmatrix} \dot{x} \\ \dot{y} \end{pmatrix} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix} + \begin{pmatrix} 0 \\ 1 \end{pmatrix} w$$

$$z = (0 \quad 1) \begin{pmatrix} x \\ y \end{pmatrix} + v$$

$$\underline{A} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix} \quad \underline{G} = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

$$\underline{H} = (0 \quad 1)$$

$$E(w(t')) = 0 \quad E(v(t)) = 0$$

$$E(w(t)w(t')) = q \delta(t-t') \quad E(v(t)v(t')) = r \delta(t-t')$$

$$\underline{Q} = q$$

$$\underline{R} = r$$

$$E(x(0)) = 0; \quad E(y(0)) = 0$$

$$E \begin{pmatrix} x^2 & x y \\ y x & y^2 \end{pmatrix}_{t=0} = \begin{pmatrix} P_{11}(0) & P_{12}(0) \\ P_{21}(0) & P_{22}(0) \end{pmatrix} = \underline{P}(0)$$

$$\dot{\underline{P}} = \underline{A} \underline{P} + \underline{P} \underline{A}^T + \underline{G} \underline{Q} \underline{G}^T - \underline{P} \underline{H}^T \underline{R}^{-1} \underline{H} \underline{P} \quad (\text{Riccati Equation})$$

$$\underline{P} = \begin{pmatrix} P_{11} & P_{12} \\ P_{21} & P_{22} \end{pmatrix} \quad P_{21} = P_{12}$$

$$\underline{A} \underline{P} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix} \begin{pmatrix} P_{11} & P_{12} \\ P_{21} & P_{22} \end{pmatrix} = \begin{pmatrix} -\alpha P_{21} & -\alpha P_{22} \\ -\beta P_{11} & -\beta P_{12} \end{pmatrix}$$

$$(\underline{A} \underline{P})^T = \underline{P} \underline{A}^T = \begin{pmatrix} -\alpha P_{21} & -\beta P_{11} \\ -\alpha P_{22} & -\beta P_{12} \end{pmatrix}$$

$$\underline{G} \underline{Q} \underline{G}^T = q \begin{pmatrix} 0 \\ 1 \end{pmatrix} \begin{pmatrix} 0 & 1 \end{pmatrix} = q \begin{pmatrix} 0 & 0 \\ 0 & 1 \end{pmatrix}$$

$$\underline{H} \underline{P} = (0 \ 1) \begin{pmatrix} P_{11} & P_{12} \\ P_{21} & P_{22} \end{pmatrix} = (P_{21}, P_{22})$$

$$(\underline{H} \underline{P})^T = \underline{P} \underline{H}^T = \begin{pmatrix} P_{21} \\ P_{22} \end{pmatrix}$$

$$\underline{P} \underline{H}^T \underline{R}^{-1} \underline{H} \underline{P} = \frac{1}{r} \begin{pmatrix} P_{21} \\ P_{22} \end{pmatrix} (P_{21}, P_{22}) = \frac{1}{r} \begin{pmatrix} P_{21}^2 & P_{21} P_{22} \\ P_{21} P_{22} & P_{22}^2 \end{pmatrix}$$

$$\dot{P}_{11} = -2\alpha P_{21} - \left(\frac{1}{r}\right) P_{21}^2 \quad P_{11}(0) \text{ given}$$

$$\dot{P}_{12} = -\alpha P_{22} - \beta P_{11} - \left(\frac{1}{r}\right) P_{21} P_{22} \quad P_{12}(0) \text{ given}$$

$$\dot{P}_{22} = -2\beta P_{12} + q - \left(\frac{1}{r}\right) P_{22}^2 \quad P_{22}(0) \text{ given}$$

Steady State:

$$\dot{P}_{11} = \dot{P}_{12} = \dot{P}_{22} = 0$$

$$\dot{P}_{11} = 0 \Rightarrow P_{21} = 0$$

$$\dot{P}_{12} = 0 \Rightarrow 0 = -\left(\alpha + \frac{1}{r} P_{21}\right) P_{22} - \beta P_{11}$$

$$\dot{P}_{22} = 0 \Rightarrow 0 = -2\beta P_{12} + q - \frac{1}{r} P_{22}^2$$

$$\text{with } P_{12} = P_{21} = 0 \Rightarrow P_{22} = (rq)^{1/2}$$

$$P_{11} = -\frac{\alpha}{\beta} P_{22} = -\left(\frac{\alpha}{\beta}\right) (rq)^{1/2}$$

$$\dot{\hat{x}} = \underline{A} \hat{x} + \underline{G} \bar{w} + \underline{P} \underline{H}^T \underline{R}^{-1} (\underline{z} - \underline{H} \hat{x}) \quad \hat{x}(0) = 0$$

or

$$\dot{\hat{x}} = (\underline{A} - \underline{K} \underline{H}) \hat{x} + \underline{K} \underline{z} \quad \underline{K} = \underline{P} \underline{H}^T \underline{R}^{-1}$$

$$\hat{x} = \begin{pmatrix} \hat{x} \\ \hat{y} \end{pmatrix}; \quad \underline{A} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix}; \quad \underline{G} = \begin{pmatrix} 0 \\ 1 \end{pmatrix} \quad \underline{H} = (0 \ 1)$$

$$\dot{\hat{x}} = -\alpha \hat{y} + \left(\frac{1}{r}\right) P_{21}(t) (z - \hat{y}) \quad \text{where } \hat{x}(0) = 0$$

$$\dot{\hat{x}} = -\alpha \hat{y} \quad \text{at steady state}$$

$$\begin{aligned} \dot{\hat{y}} &= -\beta \hat{x} + \left(\frac{1}{r}\right) P_{22}(t) (z - \hat{y}) & \hat{y}(0) &= 0 \\ &= -\beta \hat{x} + \left(\frac{q}{r}\right)^{1/2} (z - \hat{y}) & \text{at steady state} \end{aligned}$$

Summarizing the results for the case where only one state variable (y) is corrupted by noise in the systems model and measurement, the general solution satisfies the equations

$$\dot{\hat{x}} = -\alpha \hat{y} + (P_{21}(t)/r) (z - \hat{y}) \quad \hat{x}(0) = 0$$

$$\dot{\hat{y}} = -\beta \hat{x} + (P_{22}(t)/r) (z - \hat{y}) \quad \hat{y}(0) = 0$$

while the steady state equations take the form

$$\dot{\hat{x}} = -\alpha \hat{y} \quad \hat{x}(0) = 0$$

$$\dot{\hat{y}} = -\beta \hat{x} + \left(\frac{q}{r}\right)^{1/2} (z - \hat{y}) \quad \hat{y}(0) = 0$$

In the next example (example 2) we consider the case where the "plant" noise and measurement noise corrupts both state variables as follows.

Example 2:

$$\dot{x} = 0x - \alpha y + 1 w_1.$$

$$\dot{y} = -\beta x + 0y + 1 w_2.$$

$$z_1 = x + v_1$$

$$z_2 = y + v_2$$

$$\underline{z} = \begin{pmatrix} z_1 \\ z_2 \end{pmatrix}$$

$$\underline{x} = \begin{pmatrix} x \\ y \end{pmatrix}; \quad \underline{F} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix}; \quad \underline{G} = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} = \underline{I}$$

$$\dot{\underline{x}} = \underline{A} \underline{x} + \underline{I} \underline{w}$$

$$\underline{w} = \begin{pmatrix} w_1 \\ w_2 \end{pmatrix}$$

$$\underline{z} = \underline{I} \underline{x} + \underline{v}$$

$$\underline{H} = \underline{I}; \quad \underline{v} = \begin{pmatrix} v_1 \\ v_2 \end{pmatrix}$$

$$E(\underline{x}(0)) = \underline{0}$$

$$E(\underline{x}\underline{x}^T)_{t=0} = \underline{P}(0)$$

$$E(\underline{w}) = 0; E(\underline{w}(t) \underline{w}(t')^T) = \underline{Q}(t) \delta(t-t')$$

$$\underline{Q}(t) = \begin{pmatrix} Q_{11} & Q_{12} \\ Q_{21} & Q_{22} \end{pmatrix} \text{ assumed constant}$$

$$E(\underline{v}) = 0; E(\underline{v}(t) \underline{v}(t')^T) = \underline{R}(t) \delta(t-t'); \underline{R}(t) = \begin{pmatrix} R_{11} & R_{12} \\ R_{21} & R_{22} \end{pmatrix}$$

$$\underline{R}^{-1} = \frac{1}{|R|} \begin{pmatrix} R_{22} & -R_{12} \\ -R_{21} & R_{11} \end{pmatrix}$$

\underline{R} is assumed constant

$$|R| \neq 0$$

$$\underline{P} = \begin{pmatrix} P_{11} & P_{12} \\ P_{21} & P_{22} \end{pmatrix}; \quad |R| = R_{11} R_{22} - R_{21} R_{12}$$

$$\underline{G} \underline{Q} \underline{G}^T = \underline{Q}$$

$$\underline{H} \underline{P} = \underline{P}$$

$$\begin{aligned} \underline{R}^{-1} \underline{P} &= \frac{1}{|R|} \begin{pmatrix} R_{22} & -R_{12} \\ -R_{21} & R_{11} \end{pmatrix} \begin{pmatrix} P_{11} & P_{12} \\ P_{21} & P_{22} \end{pmatrix} \\ &= \frac{1}{|R|} \begin{pmatrix} P_{11} R_{22} - R_{12} P_{21} & R_{22} P_{12} - R_{12} P_{22} \\ P_{21} R_{11} - R_{21} P_{11} & R_{11} P_{22} - R_{21} P_{12} \end{pmatrix} \end{aligned}$$

$$\begin{aligned}\underline{P} \underline{R}^{-1} \underline{P} &= \frac{1}{|R|} \begin{pmatrix} P_{11} & P_{12} \\ P_{21} & P_{22} \end{pmatrix} \begin{pmatrix} P_{11} R_{22} - R_{12} P_{21} & R_{22} P_{12} - R_{12} P_{22} \\ P_{21} R_{11} - R_{21} P_{11} & R_{11} P_{22} - R_{21} P_{12} \end{pmatrix} \\ &= \frac{1}{|R|} \begin{pmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{pmatrix}\end{aligned}$$

where

$$a_{11} = P_{11} (P_{11} R_{22} - R_{12} P_{21}) + P_{12} (P_{21} R_{11} - R_{21} P_{11})$$

$$a_{12} = P_{11} (R_{22} P_{12} - R_{12} P_{22}) + P_{12} (R_{11} P_{22} - R_{21} P_{12})$$

$$a_{21} = P_{21} (P_{11} R_{22} - R_{12} P_{21}) + P_{22} (P_{21} R_{11} - R_{21} P_{11})$$

$$a_{22} = P_{12} (R_{22} P_{12} - R_{12} P_{22}) + P_{22} (R_{11} P_{22} - R_{21} P_{12})$$

for $R_{12} = R_{21}$ and $P_{21} = P_{12}$ it follows that $a_{12} = a_{21}$.

$$\underline{K} = \underline{P} \underline{H}^T \underline{R}^{-1}$$

$$\begin{aligned}&= \underline{P} \underline{R}^{-1} = \frac{1}{|R|} \begin{pmatrix} P_{11} & P_{12} \\ P_{21} & P_{22} \end{pmatrix} \begin{pmatrix} R_{22} & -R_{12} \\ -R_{21} & R_{11} \end{pmatrix} \\ &= \frac{1}{|R|} \begin{pmatrix} P_{11} R_{22} - P_{12} R_{21} & R_{11} P_{12} - R_{12} P_{11} \\ P_{21} R_{22} - P_{22} R_{21} & R_{11} P_{22} - P_{21} R_{12} \end{pmatrix} \\ &= \frac{1}{|R|} \begin{pmatrix} \xi_{11} & \xi_{12} \\ \xi_{21} & \xi_{22} \end{pmatrix}\end{aligned}$$

where

$$\xi_{11} = P_{11} R_{22} - P_{12} R_{21}$$

$$\xi_{12} = P_{12} R_{11} - P_{11} R_{12}$$

$$\xi_{21} = P_{21} R_{22} - P_{22} R_{21}$$

$$\xi_{22} = P_{22} R_{11} - P_{21} R_{12}$$

$$\underline{K}^T = \underline{R}^{-1} \underline{P}$$

$$\dot{\underline{P}} = \underline{A} \underline{P} + \underline{P} \underline{A}^T + \underline{G} \underline{Q} \underline{G}^T - \underline{K} \underline{H} \underline{P}$$

$$\underline{P}(0) = \underline{P}_0$$

$$\begin{aligned} \underline{K} \underline{H} \underline{P} &= \underline{P} \underline{I} \underline{R}^{-1} \underline{I} \underline{P} \\ &= \underline{P} \underline{R}^{-1} \underline{P} \end{aligned}$$

The Riccati equation is given by

$$\dot{\underline{P}} = \begin{pmatrix} -2\alpha P_{21} + Q_{11} - \frac{1}{|R|} a_{11} & -\beta P_{11} - \alpha P_{22} + Q_{12} - \frac{1}{|R|} a_{12} \\ -\beta P_{11} - \alpha P_{22} + Q_{21} - \frac{1}{|R|} a_{21} & -\beta P_{12} - \alpha P_{22} + Q_{21} - \frac{1}{|R|} a_{22} \end{pmatrix}$$

which for steady state $\dot{\underline{P}} = 0$ and $P_{12} \rightarrow 0$

Evaluating $\underline{P} \underline{R}^{-1}$ at steady state

$$\underline{R}^{-1} \underline{P} = \frac{1}{|R|} \begin{pmatrix} d_{11} & d_{12} \\ d_{21} & d_{22} \end{pmatrix}$$

where

$$d_{11} = R_{22} P_{11} - R_{12} P_{21}$$

$$d_{12} = R_{22} P_{12} - R_{12} P_{22}$$

$$d_{21} = R_{11} P_{21} - R_{21} P_{11}$$

$$d_{22} = P_{22} R_{11} - R_{21} P_{12}$$

$$\begin{aligned} \underline{P} \underline{R}^{-1} \underline{P} &= \frac{1}{|R|} \begin{pmatrix} P_{11} & P_{12} \\ P_{21} & P_{22} \end{pmatrix} \begin{pmatrix} d_{11} & d_{12} \\ d_{21} & d_{12} \end{pmatrix} \\ &= \frac{1}{|R|} \begin{pmatrix} P_{11} d_{11} + d_{12} P_{12} & P_{11} d_{12} + d_{22} P_{12} \\ P_{21} d_{11} + d_{21} P_{22} & P_{21} d_{12} + d_{22} P_{22} \end{pmatrix} \end{aligned}$$

$$\begin{array}{lll} \text{with } P_{12} \rightarrow 0 & d_{11} = R_{22} P_{11} & d_{21} = -R_{21} P_{11} \\ & d_{12} = -R_{12} P_{22} & d_{22} = R_{11} P_{22} \end{array}$$

at Steady state:

$$\underline{P} \underline{R}^{-1} \underline{P} = \frac{1}{|R|} \begin{pmatrix} R_{22} P_{11}^2 & -R_{12} P_{22} P_{11} \\ -R_{21} P_{11} P_{22} & R_{11} P_{22}^2 \end{pmatrix}$$

So that at steady state

$$(1) \quad 0 = -2 \alpha P_{21} + Q_{11} - \frac{1}{|R|} a_{11}$$

$$(2) \quad 0 = -\beta P_{11} - \alpha P_{22} + Q_{12} - \frac{1}{|R|} a_{12}$$

$$(3) \quad 0 = -\beta P_{11} - \alpha P_{22} + Q_{21} - \frac{1}{|R|} a_{21}$$

$$(4) \quad 0 = -2\beta P_{12} + Q_{22} - \frac{1}{|R|} a_{22}$$

Steady state: $P_{12} \longleftrightarrow 0$

$$a_{11} \longrightarrow P_{11}^2 R_{22}$$

$$a_{12} \longrightarrow -R_{12} P_{22} P_{11}$$

$$a_{21} \longrightarrow -R_{21} P_{11} P_{22}$$

$$a_{22} \longrightarrow R_{11} P_{22}^2$$

$$(1a) \quad 0 = Q_{11} - \frac{1}{|R|} R_{22} P_{11}^2$$

$$(2a) \quad 0 = -2P_{11} - \alpha P_{22} + Q_{12} + \frac{R_{12}}{|R|} P_{11} P_{22}$$

$$(3a) \quad 0 = -\beta P_{11} - \alpha P_{22} + Q_{21} + \frac{R_{12}}{|R|} P_{11} P_{22}$$

$$(4a) \quad 0 = Q_{22} - \frac{1}{|R|} R_{11} P_{22}^2$$

Thus

$$P_{11}^2 = \frac{Q_{11}}{R_{22}} |R|$$

$$(1a') \quad P_{11} = \sqrt{\frac{Q_{11}}{R_{22}} |R|} \quad \text{Steady state}$$

$$(4a') \quad P_{22} = \sqrt{\frac{Q_{22}}{R_{11}} |R|} \quad \text{Steady state}$$

$$P_{12} = P_{21} \rightarrow 0$$

The predicted state updated by measurements at an earlier time now is given by

$$\dot{\hat{\underline{x}}} = \underline{A} \hat{\underline{x}} + \underline{G} \underline{w} + \underline{P} \underline{H}^T \underline{R}^{-1} (\underline{z} - \underline{H} \hat{\underline{x}}) \quad \underline{x}(0) = 0$$

or

$$\dot{\hat{\underline{x}}} = (\underline{A} - \underline{K}) \hat{\underline{x}} + \underline{K} \underline{z}$$

$$\begin{pmatrix} \dot{\hat{x}} \\ \dot{\hat{y}} \end{pmatrix} = \begin{pmatrix} 0 & -\alpha \\ -\beta & 0 \end{pmatrix} \begin{pmatrix} \hat{x} \\ \hat{y} \end{pmatrix} + \frac{1}{|R|} \begin{pmatrix} \xi_{11} & \xi_{12} \\ \xi_{21} & \xi_{22} \end{pmatrix} \begin{pmatrix} z_1 - \hat{x} \\ z_2 - \hat{y} \end{pmatrix}$$

$$\dot{\hat{x}}(t) = -\alpha \hat{y}(t) + \frac{1}{|R|} \{ \xi_{11}(t) (z_1 - \hat{x}) + \xi_{12}(t) (z_2 - \hat{y}) \}$$

$$\dot{\hat{y}}(t) = -\beta \hat{x}(t) + \frac{1}{|R|} \{ \epsilon_{21}(t) (z_1 - \hat{x}) + \epsilon_{22}(t) (z_2 - \hat{y}) \}$$

where

$$\epsilon_{11}(t) = p_{11}(t) R_{22} - p_{12}(t) R_{21}$$

$$\epsilon_{12}(t) = p_{12}(t) R_{11} - p_{11}(t) R_{12}$$

$$\epsilon_{21}(t) = p_{21}(t) R_{22} - p_{22}(t) R_{21}$$

$$\epsilon_{22}(t) = p_{22}(t) R_{11} - p_{21}(t) R_{12}$$

$$\dot{\hat{x}} = \frac{-\epsilon_{11}(t)}{|R|} \hat{x} - \left(\alpha + \frac{\epsilon_{12}(t)}{|R|} \right) \hat{y} + \frac{\epsilon_{11}(t)}{|R|} z_1 + \frac{\epsilon_{12}(t)}{|R|} z_2$$

$$\dot{\hat{y}} = -\left(\beta + \frac{\epsilon_{21}(t)}{|R|} \right) \hat{x} - \frac{\epsilon_{22}(t)}{|R|} \hat{y} + \frac{\epsilon_{21}(t)}{|R|} z_1 + \frac{\epsilon_{22}(t)}{|R|} z_2$$

$$\underline{F_2}(t) = \begin{pmatrix} \frac{\epsilon_{11}(t)}{|R|} & -\left(\alpha + \frac{\epsilon_{12}(t)}{|R|} \right) \\ -\left(\beta + \frac{\epsilon_{21}(t)}{|R|} \right) & \frac{\epsilon_{22}(t)}{|R|} \end{pmatrix} = \underline{A}(t) - \underline{K}(t)$$

$$\dot{\hat{x}} = \underline{F_2}(t) \hat{x} + \underline{B} z$$

$$\hat{x} = \begin{pmatrix} \hat{x} \\ \hat{y} \end{pmatrix}; z = \begin{pmatrix} z_1 \\ z_2 \end{pmatrix}$$

$$\underline{B} = \begin{pmatrix} \frac{\epsilon_{11}(t)}{|R|} & \frac{\epsilon_{12}(t)}{|R|} \\ \frac{\epsilon_{21}(t)}{|R|} & \frac{\epsilon_{22}(t)}{|R|} \end{pmatrix} = \underline{K}(t)$$

$$\hat{\underline{x}}(t) = \underline{\Phi}(t, t_0) \hat{\underline{x}}(t_0) + \int_{t_0}^t \underline{\Phi}(t, \tau) \underline{K}(\tau) \underline{z}(\tau) d\tau$$

where $\underline{\Phi}(t, t_0)$ satisfies the homogeneous equation

$$\dot{\underline{\Phi}}(t, t_0) = \underline{F}_2(t) \underline{\Phi}(t, t_0)$$

Accordingly we have obtained either the differential equation for which the predicted estimate $\hat{\underline{x}}$ needs to satisfy or the integral solution for this estimate in terms of its transition matrix $\underline{\Phi}(t, t_0)$.



DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Commander Defense Technical Information Center ATTN: DTIC-DDAC Cameron Station, Bldg 5 Alexandria, VA 22304-6145	2	Commander US Army Development and Employment Agency ATTN: MODE-TED-SAB (2 cys) Ft. Lewis, WA 98433-5000
2	Commander US Army Materiel Command ATTN: AMXPA AMCDMA-M 5001 Eisenhower Avenue Alexandria, VA 22333-0001	4	Director US Army TRADOC Systems Analysis Activity ATTN: ATOR-TSL ATOR-T ATOR-TE ATOR-TF White Sands Missile Range NM 88002-5502
1	Director Combat Data Information Center AFWAL/FIES/CDIC Wright-Patterson AFB OH 45433-5000	1	Commandant US Army Infantry School ATTN: ATSH-CD-CS-OR Fort Benning, GA 31905-5400
1	Pentagon Library ATTN: AN-AL-RS (Army Studies) Pentagon, Room 1A518 Wash, DC 20310	3	Commander US Army Tank-Automotive Command ATTN: AMSTA-Z (Tech Lib) AMSTA-ZE AMSTA-ZS- Warren, MI 48090
1	Commander US Army Concepts Analysis Agency ATTN: OSCA-M51-L 8120 Woodmont Avenue Bethesda, MD 20814-2797	1	HQDA (DACS-CV) Washington, DC 20310
2	General Dynamics Land Systems Division ATTN: Mr. Payer/Mr. J. O'Rourke P.O. Box 1800 Warren, MI 48090	2	Project Manager M1E1 Tank System ATTN: AMCPW-M1E1 Warren, MI 48090

DISTRIBUTION LIST (continued)

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
<u>Aberdeen Proving Ground</u>			
1	Dir, BRL ATTN: AMXBR-OD-ST Bldg 305 Aberdeen Proving Ground, MD 21005-5066	7	Director, AMSAA ATTN: AMXSY-G AMXSY-GA (W. Brooks/ E. Christman/B. Siegel/ R. Conroy) AMXSY-GS (B. Blankenbiller) AMXSY-C (H. Burke) APG, MD 21005-5071
2	Dir, BRL, Bldg 328 ATTN: AMXBR-OD AMXBR-SECAD (Dr. Jonnson/ Dr. Wolfe) Aberdeen Proving Ground, MD 21005-5066		

GIST

	TITLE _____	
	BRIEFING _____ REPORT <u>X</u>	

THE PRINCIPAL FINDINGS and recommendations of the work reported herein are as follows:

Combined Arms Lanchester Modeling of Warfare can be enhanced by using techniques of modern control theory to afford battlefield commanders improved forecast of battle.

THE MAIN ASSUMPTIONS on which the work reported herein rests are as follows:

Linear model of warfare corrupted by gaussian white noise with measurement noise constrained to gaussian white noise.

THE PRINCIPAL LIMITATIONS of this work which may affect the findings are as follows:

Need reasonable estimates of initial conditions and properties of noise corrupting both math model and measurements of battle.

THE SCOPE OF THE STUDY

Applicable to wide range of land warfare models including combined arms.

THE STUDY OBJECTIVE

Enhance appreciation that modern control can play a key role in modeling land warfare.

THE BASIC APPROACH

Math modeling using Kalman-Bucy filtering of control theory.

THE REASONS FOR PERFORMING THE STUDY

Call attention to the fact that modern control theory provides and improved capability to provide forecasts of status of battle.

STUDY IMPACT STATEMENT (Actual or expected changes in operations realized from implementation of study results -- if possible state in quantitative terms.) May provide improved estimates of status of battle.



THE STUDY SPONSOR

N/A

ADDRESS FOR COMMENTS AND QUESTIONS

DTIC/DLSIE ACCESSION NUMBER OF FINAL REPORT

GIST

	<p>TITLE _____</p> <p>BRIEFING _____</p> <p>REPORT <u>X</u></p>	
---	---	---

THE PRINCIPAL FINDINGS and recommendations of the work reported herein are as follows:

Combined Arms Lanchester Modeling of Warfare can be enhanced by using techniques of modern control theory to afford battlefield commanders improved forecast of battle.

THE MAIN ASSUMPTIONS on which the work reported herein rests are as follows:

Linear model of warfare corrupted by gaussian white noise with measurement noise constrained to gaussian white noise.

THE PRINCIPAL LIMITATIONS of this work which may affect the findings are as follows:

Need reasonable estimates of initial conditions and properties of noise corrupting both math model and measurements of battle.

THE SCOPE OF THE STUDY

Applicable to wide range of land warfare models including combined arms.

THE STUDY OBJECTIVE

Enhance appreciation that modern control can play a key role in modeling land warfare.

THE BASIC APPROACH

Math modeling using Kalman-Bucy filtering of control theory.

THE REASONS FOR PERFORMING THE STUDY

Call attention to the fact that modern control theory provides and improved capability to provide forecasts of status of battle.

STUDY IMPACT STATEMENT (Actual or expected changes in operations realized from implementation of study results -- if possible state in quantitative terms.) May provide improved estimates of status of battle.



THE STUDY SPONSOR

N/A

ADDRESS FOR COMMENTS AND QUESTIONS

DTIC/DLSIE ACCESSION NUMBER OF FINAL REPORT

GIST

	<p>TITLE _____</p> <p>BRIEFING _____</p>	 <p>REPORT <u>X</u></p>
---	--	--

THE PRINCIPAL FINDINGS and recommendations of the work reported herein are as follows:

Combined Arms Lanchester Modeling of Warfare can be enhanced by using techniques of modern control theory to afford battlefield commanders improved forecast of battle.

THE MAIN ASSUMPTIONS on which the work reported herein rests are as follows:

Linear model of warfare corrupted by gaussian white noise with measurement noise constrained to gaussian white noise.

THE PRINCIPAL LIMITATIONS of this work which may affect the findings are as follows:

Need reasonable estimates of initial conditions and properties of noise corrupting both math model and measurements of battle.

THE SCOPE OF THE STUDY

Applicable to wide range of land warfare models including combined arms.

THE STUDY OBJECTIVE

Enhance appreciation that modern control can play a key role in modeling land warfare.

THE BASIC APPROACH

Math modeling using Kalman-Bucy filtering of control theory.

THE REASONS FOR PERFORMING THE STUDY

Call attention to the fact that modern control theory provides and improved capability to provide forecasts of status of battle.

STUDY IMPACT STATEMENT (Actual or expected changes in operations realized from implementation of study results -- if possible state in quantitative terms.) May provide improved estimates of status of battle.



THE STUDY SPONSOR

N/A

ADDRESS FOR COMMENTS AND QUESTIONS

DTIC/DLSIE ACCESSION NUMBER OF FINAL REPORT

GIST

 AMSAA	TITLE _____ BRIEFING _____	 REPORT <u>X</u>
--	-----------------------------------	--

THE PRINCIPAL FINDINGS and recommendations of the work reported herein are as follows:

Combined Arms Lanchester Modeling of Warfare can be enhanced by using techniques of modern control theory to afford battlefield commanders improved forecast of battle.

THE MAIN ASSUMPTIONS on which the work reported herein rests are as follows:

Linear model of warfare corrupted by gaussian white noise with measurement noise constrained to gaussian white noise.

THE PRINCIPAL LIMITATIONS of this work which may affect the findings are as follows:

Need reasonable estimates of initial conditions and properties of noise corrupting both math model and measurements of battle.

THE SCOPE OF THE STUDY

Applicable to wide range of land warfare models including combined arms.

THE STUDY OBJECTIVE

Enhance appreciation that modern control can play a key role in modeling land warfare.

THE BASIC APPROACH

Math modeling using Kalman-Bucy filtering of control theory.

THE REASONS FOR PERFORMING THE STUDY

Call attention to the fact that modern control theory provides an improved capability to provide forecasts of status of battle.

STUDY IMPACT STATEMENT (Actual or expected changes in operations realized from implementation of study results -- if possible state in quantitative terms.) May provide improved estimates of status of battle.



THE STUDY SPONSOR

17/1

ADDRESS FOR COMMENTS AND QUESTIONS

DTIC/DLSIE ACCESSION NUMBER OF FINAL REPORT

GIST

	<p>TITLE _____</p> <p>BRIEFING _____</p> <p>REPORT <u>X</u></p>	
---	---	---

THE PRINCIPAL FINDINGS and recommendations of the work reported herein are as follows:

Combined Arms Lanchester Modeling of Warfare can be enhanced by using techniques of modern control theory to afford battlefield commanders improved forecast of battle.

THE MAIN ASSUMPTIONS on which the work reported herein rests are as follows:

Linear model of warfare corrupted by gaussian white noise with measurement noise constrained to gaussian white noise.

THE PRINCIPAL LIMITATIONS of this work which may affect the findings are as follows:

Need reasonable estimates of initial conditions and properties of noise corrupting both math model and measurements of battle.

THE SCOPE OF THE STUDY

Applicable to wide range of land warfare models including combined arms.

THE STUDY OBJECTIVE

Enhance appreciation that modern control can play a key role in modeling land warfare.

THE BASIC APPROACH

Math modeling, using Kalman-Bucy filtering of control theory.

THE REASONS FOR PERFORMING THE STUDY

Call attention to the fact that modern control theory provides an improved capability to provide forecasts of status of battle.

STUDY IMPACT STATEMENT (Actual or expected changes in operations realized from implementation of study results -- if possible state in quantitative terms.) May provide improved estimates of status of battle.



THE STUDY SPONSOR

N/A

ADDRESS FOR COMMENTS AND QUESTIONS

DTIC/DLSIE ACCESSION NUMBER OF FINAL REPORT

GIST

	<p>TITLE _____</p> <p>BRIEFING _____</p> <p>REPORT <u>X</u></p>	
---	---	---

THE PRINCIPAL FINDINGS and recommendations of the work reported herein are as follows:

Combined Arms Lanchester Modeling of Warfare can be enhanced by using techniques of modern control theory to afford battlefield commanders improved forecast of battle.

THE MAIN ASSUMPTIONS on which the work reported herein rests are as follows:
Linear model of warfare corrupted by gaussian white noise with measurement noise constrained to gaussian white noise.

THE PRINCIPAL LIMITATIONS of this work which may affect the findings are as follows:

Need reasonable estimates of initial conditions and properties of noise corrupting both math model and measurements of battle.

THE SCOPE OF THE STUDY

Applicable to wide range of land warfare models including combined arms.

THE STUDY OBJECTIVE

Enhance appreciation that modern control can play a key role in modeling land warfare.

THE BASIC APPROACH

Math modeling using Kalman-Bucy filtering of control theory.

THE REASONS FOR PERFORMING THE STUDY

Call attention to the fact that modern control theory provides and improved capability to provide forecasts of status of battle.

STUDY IMPACT STATEMENT (Actual or expected changes in operations realized from implementation of study results -- if possible state in quantitative terms.) May provide improved estimates of status of battle.

THE STUDY SPONSOR

N/A

ADDRESS FOR COMMENTS AND QUESTIONS

DTIC/DLSIE ACCESSION NUMBER OF FINAL REPORT

DTIC

END

4-86